

SAFETY DATA SHEET

Version 8.12
Revision Date 30.04.2024
Print Date 27.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifiers**

Product name : Ethyl Ether Anhydrous GR ACS

Product Number : EX0190
Catalogue No. : FX0149
Brand : Millipore
Index-No. : 603-022-00-4
CAS-No. : 60-29-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis

1.3 Details of the supplier of the safety data sheet

Company : MilliporeSigma Canada Ltd.
2149 WINSTON PARK DRIVE
OAKVILLE ON L6H 6J8
CANADA

Telephone : +1 905 829-9500
Fax : +1 905 829-9292

1.4 Emergency telephone

Emergency Phone # : +1-703-527-3887 CHEMTREC
(International)
24 Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)**

Flammable liquids (Category 1), H224
Acute toxicity, Oral (Category 4), H302
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336
For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Millipore - EX0190

Page 1 of 13

Signal Word	Danger
Hazard Statements	
H224	Extremely flammable liquid and vapor.
H302	Harmful if swallowed.
H336	May cause drowsiness or dizziness.
Precautionary Statements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist or vapors.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides.

Repeated exposure may cause skin dryness or cracking.

- none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₄ H ₁₀ O
Molecular weight	: 74.12 g/mol
CAS-No.	: 60-29-7
EC-No.	: 200-467-2
Index-No.	: 603-022-00-4

Component	Classification	Concentration *
-----------	----------------	--------------------

Millipore - EX0190

Page 2 of 13

Diethyl ether		
	Flam. Liq. 1; Acute Tox. 4; STOT SE 3; H224, H302, H336 Concentration limits: >= 20 %: STOT SE 3, H336;	<= 100 %
* Weight %		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Millipore - EX0190

Page 3 of 13

Vapors are heavier than air and may spread along floors.
Development of hazardous combustion gases or vapours possible in the event of fire.
Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Ingredients with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Basis
Diethyl ether	60-29-7	TWA	400 ppm 1,210 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	500 ppm 1,520 mg/m ³	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	400 ppm	Canada. British Columbia OEL
		STEL	500 ppm	Canada. British Columbia OEL
		TWAEV	400 ppm 1,210 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		STEV	500 ppm 1,520 mg/m ³	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	400 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	500 ppm	USA. ACGIH Threshold Limit Values (TLV)

8.2 Exposure controls**Appropriate engineering controls**

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 30 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter type AX

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|--|---|
| a) Appearance | Form: liquid
Color: colorless |
| b) Odor | sweet, ether-like |
| c) Odor Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point: -116 °C (-177 °F) |
| f) Initial boiling point and boiling range | 34.6 °C 94.3 °F at 1,013 hPa |
| g) Flash point | -40 °C (-40 °F) - closed cup - DIN 51755 Part 1 |
| h) Evaporation rate | No data available |

- | | |
|---|--|
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 36 %(V)
Lower explosion limit: 1.7 %(V) |
| k) Vapor pressure | 189 hPa at 0 °C (32 °F)
389 hPa at 10 °C(50 °F)
563 hPa at 20 °C(68 °F)
863 hPa at 30 °C(86 °F)
1,228 hPa at 40 °C(104 °F)
2,311 hPa at 60 °C(140 °F) |
| l) Vapor density | 2.56 - (Air = 1.0) |
| m) Density | 0.71 g/cm ³ at 20 °C (68 °F) |
| Relative density | No data available |
| n) Water solubility | 65 g/l at 20 °C (68 °F) - completely soluble |
| o) Partition coefficient: n-octanol/water | log Pow: 1.1 - Bioaccumulation is not expected. |
| p) Autoignition temperature | 175 °C (347 °F) at 1,013.25 hPa |
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | Not classified as explosive. |
| t) Oxidizing properties | none |

9.2 Other safety information

Relative vapor density	2.56 - (Air = 1.0)
------------------------	--------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

Formation of peroxides possible.
Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .
Contains the following stabilizer(s):
ethanol (0.05 %)

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:
chromyl chloride
Peroxides
Risk of explosion with:

Millipore - EX0190

Page 7 of 13

azides
halogens
halogen-halogen compounds
nonmetallic oxyhalides
Strong oxidizing agents
chromium(VI) oxide
halogen oxides
peroxi compounds
perchloric acid
perchlorates
Nitric acid
nitrating acid
Oxygen
Ozone
turpentine oils and/or turpentine substitutes
nitrates
metallic chlorides
salts of oxyhalogenic acids
nitrogen oxides
nonmetallic oxides
chromosulfuric acid
chlorates
hydrogen peroxide
permanganic acid
sulfuric acid
with
Nitric acid
sulfur
Risk of explosion during distillation.
Exothermic reaction with:
acid halides

10.4 Conditions to avoid

Warming.
Moisture.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Peroxides
In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 1,212 mg/kg
(Calculation method)

LD50 Oral - Rat - 1,211 mg/kg

Remarks: (RTECS)

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis.

LC50 Inhalation - Mouse - 4 h - 97.5 mg/l - vapor

Remarks: (RTECS)

Symptoms: mucosal irritations

LD50 Dermal - Rabbit - male - > 20,000 mg/kg

(OECD Test Guideline 402)

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h

(OECD Test Guideline 404)

Remarks: Dermatitis

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

(OECD Test Guideline 405)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Micronucleus test

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 487

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Red blood cells (erythrocytes)
Application Route: Intraperitoneal
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Oral - May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - NOAEL (No observed adverse effect level) - 500 mg/kg - LOAEL (Lowest observed adverse effect level) - 2,000 mg/kg

Remarks: (ECHA)

Inhalation may provoke the following symptoms:

Cough, chest pain, Difficulty in breathing, Dizziness, Drowsiness, Contact with eyes can cause:, Redness, Provokes tears., Blurred vision, Prolonged or repeated exposure to skin causes defatting and dermatitis.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Narcotic!

After absorption:

Salivation

ataxia (impaired locomotor coordination)

inebriation

Unconsciousness

Coma

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Liver - Ingestion may provoke the following symptoms:, Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	LC50 - <i>Lepomis macrochirus</i> (Bluegill sunfish) - > 10,000 mg/l - 96 h Remarks: (IUCLID)
Toxicity to daphnia and other aquatic invertebrates	EC50 - <i>Daphnia magna</i> (Water flea) - 1,380 mg/l - 48 h Remarks: (IUCLID)
Toxicity to algae	static test ErC50 - <i>Desmodesmus subspicatus</i> (green algae) - > 100 mg/l - 72 h (OECD Test Guideline 201) static test NOEC - <i>Desmodesmus subspicatus</i> (green algae) - 100 mg/l - 72 h (OECD Test Guideline 201)
Toxicity to bacteria	static test EC50 - activated sludge - 21,000 mg/l - 3 h (OECD Test Guideline 209) static test NOEC - activated sludge - 42 mg/l - 3 h (OECD Test Guideline 209)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	semi-static test NOEC - <i>Daphnia magna</i> (Water flea) - > 100 mg/l - 21 d (OECD Test Guideline 211)

12.2 Persistence and degradability

Not readily biodegradable.

12.3 Bioaccumulative potential

No bioaccumulation is to be expected (log Pow ≤ 4).

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information

TDG

UN number: 1155 Class: 3 Packing group: I
Proper shipping name: DIETHYL ETHER
Labels: 3
ERG Code: 127
Marine pollutant: no

IMDG

UN number: 1155 Class: 3 Packing group: I EMS-No: F-E, S-D
Proper shipping name: DIETHYL ETHER

IATA

UN number: 1155 Class: 3 Packing group: I
Proper shipping name: Diethyl ether

SECTION 15: Regulatory information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

SECTION 16: Other information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.12

Revision Date: 30.04.2024

Print Date: 27.07.2024

